

BK 823 - Especificaciones técnicas



Description

BK 823 es un neumático proyectado especialmente para tractores maquinaria agrícola y remolques para el cultivo del suelo y las aplicaciones de transporte tanto por carretera como en el campo. El especial dibujo con bloques de la banda de rodadura hace que sea particularmente idóneo para operaciones pesadas que requieren un óptimo giro de dirección. Está disponible también como versión HD que asegura una resistencia a los cortes y las laceraciones.

UM

US Standard

Construction

 BIAS

Machinery

Agricultura: Maquinaria agrícola • Tractor • Remolque

Version	HD
Type	TT
Tyre Size	9.00 - 16
LI/SS	127 A8

Dimensions US Standard

Usa code	94049202
Ply Rating	14
Section Width (inch)	9.6
Overall Diameter (inch)	35.1
Static Loaded Radius (inch)	15.5
Rolling Circumference (inch)	101.7
Rim Rec	6.5
ECE	E11-106R-004338

Load capacity (lbs)

mph / psi	64
25	3860

Printed on 23/04/2024 10:16

All product data contained in this publication are for information purposes only and may be modified at any time without prior notice. Balkrishna Industries Ltd. or any of its subsidiary companies does not undertake any responsibility or liability for undetected errors and/or misprints. All rights reserved. The materials and contents of this publication and the website are the exclusive property of Balkrishna Industries Ltd. and are protected by industrial and/or intellectual property laws. The user is not permitted to copy, reproduce, transfer, upload, make use of, publish or spread any contents, in whole or in part, on paper format, electronic format or otherwise without prior written consent by Balkrishna Industries Ltd..