

## BK 823 - Ficha técnica



### Description

BK 823 es un neumático proyectado especialmente para tractores maquinaria agrícola y remolques para el cultivo del suelo y las aplicaciones de transporte tanto por carretera como en el campo. El especial dibujo con bloques de la banda de rodadura hace que sea particularmente idóneo para operaciones pesadas que requieren un óptimo giro de dirección. Está disponible también como versión HD que asegura una resistencia a los cortes y las laceraciones.

### UM

US Standard

### Construction

❖ BIAS

### Machinery

Agricultura: Maquinaria agrícola • Tractor • Remolque

SIZE	Version	USACode	LI/SS	PR	RIM REC	RIM ALT	SW	OD	SLR	RC	Type	ECE
9.00 - 16	HD	94049202	127 A8	14	6.5		9.6	35.1	15.5	101.7	TT	E11-106R-004338
9.00 - 16	STANDARD	94042432	124 A8	12	6.5		9.6	35.1	15.5	101.7	TT	E11-106R-003603
9.00 - 16	STANDARD	94040131	127 A8	14	6.5		9.6	35.1	15.5	101.7	TT	E11-106R-003604
9.00 - 16	STANDARD	94060252	121 A8	10	6.5		9.6	35.1	15.5	101.7	TL	

Printed on 23/04/2024 10:42

All product data contained in this publication are for information purposes only and may be modified at any time without prior notice. Balkrishna Industries Ltd. or any of its subsidiary companies does not undertake any responsibility or liability for undetected errors and/or misprints. All rights reserved. The materials and contents of this publication and the website are the exclusive property of Balkrishna Industries Ltd. and are protected by industrial and/or intellectual property laws. The user is not permitted to copy, reproduce, transfer, upload, make use of, publish or spread any contents, in whole or in part, on paper format, electronic format or otherwise without prior written consent by Balkrishna Industries Ltd..