

## BK 826 - Especificaciones técnicas



### Description

BK 826 ha sido proyectado especialmente para los remolques utilizados en las operaciones de transporte. Es un neumático diagonal caracterizado por una elevada capacidad de carga gracias a la carcasa reforzada. BK 826 está disponible también como versión "industrial" ya que ofrece una particular resistencia a los cortes y también es idóneo para cargadoras retroexcavadoras.

### UM

International Standard

### Construction

 BIAS

### Machinery

Agricultura: Remolque

Industrial: Cargadora retroexcavadora • Remolque

Version	STANDARD
Type	TT
Tyre Size	8.25 - 16

## Dimensions International Standard

Ply Rating	14
Section Width (mm)	238
Overall Diameter (mm)	863
Rim Rec	6.50 H
Rim Alt	6.00 G
ECE	E4-54R-0024095

## Load capacity (Kg)

km/h / bar	6.90
100 LS	1745
100 LD	1650

Printed on 27/04/2024 10:29

All product data contained in this publication are for information purposes only and may be modified at any time without prior notice. Balkrishna Industries Ltd. or any of its subsidiary companies does not undertake any responsibility or liability for undetected errors and/or misprints. All rights reserved. The materials and contents of this publication and the website are the exclusive property of Balkrishna Industries Ltd. and are protected by industrial and/or intellectual property laws. The user is not permitted to copy, reproduce, transfer, upload, make use of, publish or spread any contents, in whole or in part, on paper format, electronic format or otherwise without prior written consent by Balkrishna Industries Ltd..