

BK 826 - Especificaciones técnicas



Description

BK 826 ha sido proyectado especialmente para los remolques utilizados en las operaciones de transporte. Es un neumático diagonal caracterizado por una elevada capacidad de carga gracias a la carcasa reforzada. BK 826 está disponible también como versión "industrial" ya que ofrece una particular resistencia a los cortes y también es idóneo para cargadoras retroexcavadoras.

UM

US Standard

Construction

 BIAS

Machinery

Agricultura: Remolque

Industrial: Cargadora retroexcavadora • Remolque

Version	STANDARD
Type	TT
Tyre Size	8.25 - 16

Dimensions US Standard

Usa code	94013289
Ply Rating	8
Section Width (inch)	9.4
Overall Diameter (inch)	34
Rim Rec	6.50 H
Rim Alt	6.00 G

Load capacity (lbs)

mph / psi	61
62 LS	2975
62 LD	2810

Printed on 27/04/2024 3:57

All product data contained in this publication are for information purposes only and may be modified at any time without prior notice. Balkrishna Industries Ltd. or any of its subsidiary companies does not undertake any responsibility or liability for undetected errors and/or misprints. All rights reserved. The materials and contents of this publication and the website are the exclusive property of Balkrishna Industries Ltd. and are protected by industrial and/or intellectual property laws. The user is not permitted to copy, reproduce, transfer, upload, make use of, publish or spread any contents, in whole or in part, on paper format, electronic format or otherwise without prior written consent by Balkrishna Industries Ltd..