

## BK-LOADER 53 - Especificaciones técnicas



### Description

BK-LOADER 53 es un neumático con cinturones de aramida desarrollado para las palas cargadoras utilizadas en las aplicaciones industriales. El dibujo especial de la banda de rodadura garantiza una óptima estabilidad lateral, además, gracias a la banda de rodadura extra profunda también se obtiene una extraordinaria resistencia al desgaste, a los cortes y a los pinchazos. BK-LOADER 53 se caracteriza por sus excepcionales propiedades de auto-limpieza, así como por su excelente agarre y tracción sobre las superficies mojadas y secas. Por último, este neumático es particularmente adecuado para las operaciones de reciclaje.

### UM

US Standard

### Construction

 RADIAL

### Machinery

Industrial: Pala cargadora

|           |               |
|-----------|---------------|
| Version   | ARAMID BELTED |
| Type      | TL            |
| Tyre Size | 405/70 R 20   |
| LI/SS     | 155A2/151A4   |

## Dimensions US Standard

|                              |                         |
|------------------------------|-------------------------|
| Usa code                     | 94054428                |
| Section Width (inch)         | 16                      |
| Overall Diameter (inch)      | 43.2                    |
| Static Loaded Radius (inch)  | 20.1                    |
| Rolling Circumference (inch) | 131.5                   |
| Rim Rec                      | 13                      |
| Rim Alt                      | 14 ; 13 SDC; 12 ;12 SDC |

## Load capacity (lbs)

| mph / psi | 22   | 29   | 36   | 44   | 51   | 58    | 65    | 73    | 80    |
|-----------|------|------|------|------|------|-------|-------|-------|-------|
| 12        | 2670 | 3350 | 3980 | 4610 | 5240 | 5820  | 6400  | 6990  | 7610  |
| 5         | 3030 | 3800 | 4520 | 5240 | 5950 | 6610  | 7270  | 7940  | 8540  |
| Static    | 4850 | 6060 | 7220 | 8380 | 9530 | 10580 | 11680 | 12680 | 13670 |

Printed on 24/04/2024 12:11

All product data contained in this publication are for information purposes only and may be modified at any time without prior notice. Balkrishna Industries Ltd. or any of its subsidiary companies does not undertake any responsibility or liability for undetected errors and/or misprints. All rights reserved. The materials and contents of this publication and the website are the exclusive property of Balkrishna Industries Ltd. and are protected by industrial and/or intellectual property laws. The user is not permitted to copy, reproduce, transfer, upload, make use of, publish or spread any contents, in whole or in part, on paper format, electronic format or otherwise without prior written consent by Balkrishna Industries Ltd..