

BK RUF N TUF - Especificaciones técnicas



Description

BK RUF N TUF es un neumático que en la banda de rodadura presenta un dibujo con bloques, idóneo para operaciones de transporte con remolques y camionetas. Es ideal para utilizarlo por carretera y garantiza una óptima duración.

UM

US Standard

Construction

 BIAS

Machinery

Agricultura: Camión ligero • Remolque

Version	STANDARD
Type	TT
Tyre Size	7.50 - 16

Dimensions US Standard

Usa code	94014033
Ply Rating	8
Section Width (inch)	8.5
Overall Diameter (inch)	32.7
Rim Rec	6.00 G
Rim Alt	5.50 F

Load capacity (lbs)

	mph / psi	-
	-	-
	-	-

Printed on 27/04/2024 7:10

All product data contained in this publication are for information purposes only and may be modified at any time without prior notice. Balkrishna Industries Ltd. or any of its subsidiary companies does not undertake any responsibility or liability for undetected errors and/or misprints. All rights reserved. The materials and contents of this publication and the website are the exclusive property of Balkrishna Industries Ltd. and are protected by industrial and/or intellectual property laws. The user is not permitted to copy, reproduce, transfer, upload, make use of, publish or spread any contents, in whole or in part, on paper format, electronic format or otherwise without prior written consent by Balkrishna Industries Ltd..