

COMMANDER 3 RIB - Especificaciones técnicas



Description

COMMANDER 3 RIB es un neumático anterior con una nervadura de la banda de rodadura con 3 costillas idóneo para los trabajos del campo y las operaciones de transporte. Este neumático ofrece una excelente durabilidad y una elevada capacidad de carga, gracias a la distribución de la carga optimizada en las costillas, en la parte central y en el área del hombro. Su robusta carcasa y una mezcla particularmente resistente a los cortes y las laceraciones aseguran una extraordinaria resistencia a los pinchazos.

UM

International Standard

Construction

 BIAS

Machinery

Agricultura: Tractor 2WD

Version	STANDARD
Type	TT
Tyre Size	7.50 - 16
LI/SS	103 A6

Dimensions International Standard

Ply Rating	8
Section Width (mm)	212
Overall Diameter (mm)	810
Rim Rec	5.50 F
Rim Alt	5.00 F ; 5 K ; 6.00 F
TRA Code	F2

Load capacity (Kg)

km/h / bar	3.70
30	875

Rolling Circumference & SLR values are at rated Load and inflation pressure. These values may vary at different Load and pressure condition.

Printed on 05/11/2024 8:57

All product data contained in this publication are for information purposes only and may be modified at any time without prior notice. Balkrishna Industries Ltd. or any of its subsidiary companies does not undertake any responsibility or liability for undetected errors and/or misprints. All rights reserved. The materials and contents of this publication and the website are the exclusive property of Balkrishna Industries Ltd. and are protected by industrial and/or intellectual property laws. The user is not permitted to copy, reproduce, transfer, upload, make use of, publish or spread any contents, in whole or in part, on paper format, electronic format or otherwise without prior written consent by Balkrishna Industries Ltd..