

## DON 2000 - Especificaciones técnicas



### Description

DON 2000 es un neumático idóneo para realizar operaciones de transporte con remolques y camionetas tanto por carretera como fuera de carretera. Asegura una extraordinaria durabilidad, así como elevadas prestaciones durante todo el ciclo de vida del producto.

### UM

International Standard

### Construction

 BIAS

### Machinery

Agricultura: Camión ligero • Remolque

Version	STANDARD
Type	TT
Tyre Size	12.00 - 20

## Dimensions International Standard

<b>Ply Rating</b>	18
<b>Section Width (mm)</b>	315
<b>Overall Diameter (mm)</b>	1145
<b>Static Loaded Radius (mm)</b>	535
<b>Rolling Circumference (mm)</b>	3519
<b>Rim Rec</b>	8.5
<b>Rim Alt</b>	9.0

## Load capacity (Kg)

	km/h / bar	7.95	7.25
100 LS		3750	-
100 LD		-	3350

Printed on 27/02/2024 4:38

All product data contained in this publication are for information purposes only and may be modified at any time without prior notice. Balkrishna Industries Ltd. or any of its subsidiary companies does not undertake any responsibility or liability for undetected errors and/or misprints. All rights reserved. The materials and contents of this publication and the website are the exclusive property of Balkrishna Industries Ltd. and are protected by industrial and/or intellectual property laws. The user is not permitted to copy, reproduce, transfer, upload, make use of, publish or spread any contents, in whole or in part, on paper format, electronic format or otherwise without prior written consent by Balkrishna Industries Ltd..