

# EARTHMAX CRUSHER HAUL - Especificaciones técnicas



## Description

EARTHMAX CRUSHER HAUL es un neumático radial All Steel particularmente proyectado para las aplicaciones de transporte por carretera e fuera de carretera, así como operaciones en las minas. Este neumático se caracteriza para una avanzada durabilidad y un mejor kilometraje. El dibujo de bloques de la banda de rodadura garantiza una excelente tracción. Además, EARTHMAX CRUSHER HAUL ofrece un extraordinario confort de conducción, un elevado nivel de maniobrabilidad y menor fatiga de conductor.

## UM

US Standard

## Construction

 RADIAL

## Machinery

OTR: Volquete

Version	STANDARD
Type	TT
Tyre Size	10.00 R 20
LI/SS	149/146 J

## Dimensions US Standard

Usa code	94070558
Ply Rating	18
Overall Width (inch)	10.7
Overall Diameter (inch)	41.9
Rim Rec	7.50
Rim Alt	8.00

## Load capacity (lbs)

mph / psi	120
62 Load Single	7165
62 Load Dual	6615

Printed on 27/04/2024 9:31

All product data contained in this publication are for information purposes only and may be modified at any time without prior notice. Balkrishna Industries Ltd. or any of its subsidiary companies does not undertake any responsibility or liability for undetected errors and/or misprints. All rights reserved. The materials and contents of this publication and the website are the exclusive property of Balkrishna Industries Ltd. and are protected by industrial and/or intellectual property laws. The user is not permitted to copy, reproduce, transfer, upload, make use of, publish or spread any contents, in whole or in part, on paper format, electronic format or otherwise without prior written consent by Balkrishna Industries Ltd..