

EARTHMAX CRUSHER HAUL - Ficha técnica



Description

EARTHMAX CRUSHER HAUL es un neumático radial All Steel particularmente proyectado para las aplicaciones de transporte por carretera e fuera de carretera, así como operaciones en las minas. Este neumático se caracteriza para una avanzada durabilidad y un mejor kilometraje. El dibujo de bloques de la banda de rodadura garantiza una excelente tracción. Además, EARTHMAX CRUSHER HAUL ofrece un extraordinario confort de conducción, un elevado nivel de maniobrabilidad y menor fatiga de conductor.

UM

US Standard

Construction

RADIAL

Machinery

OTR: Volquete

SIZE	Version	USACode	LI/SS	RIM REC	RIM ALT	OW	OD	SLR	RC	Type
10.00 R 20	STANDARD	94070558	149/146 J	7.50	8.00	10.7	41.9	0	0	TT
11.00 R 20	STANDARD	94070565	152/149 J	8.00	8.50	11.4	43.4	0	0	TT
12.00 R 24	STANDARD	94075959	160/156 K	8.50	9.00	12.2	48.4	22.2	149	TT
12.00 R 24	STANDARD	94075966	160/156 K	8.50	9.00	12.2	48.4	22.2	149	TL

Rolling Circumference & SLR values are at rated Load and inflation pressure. These values may vary at different Load and pressure condition.

Printed on 09/12/2024 11:12

All product data contained in this publication are for information purposes only and may be modified at any time without prior notice. Balkrishna Industries Ltd. or any of its subsidiary companies does not undertake any responsibility or liability for undetected errors and/or misprints. All rights reserved. The materials and contents of this publication and the website are the exclusive property of Balkrishna Industries Ltd. and are protected by industrial and/or intellectual property laws. The user is not permitted to copy, reproduce, transfer, upload, make use of, publish or spread any contents, in whole or in part, on paper format, electronic format or otherwise without prior written consent by Balkrishna Industries Ltd..