

EARTHMAX SR 22 AS - Especificaciones técnicas



Description

EARTHMAX SR 22 AS (E-2**/G-2*/L-2**) es un neumático radial All Steel diseñado especialmente para niveladoras, pequeñas cargadoras y camiones en condiciones de hielo y nieve, pero garantiza un rendimiento óptimo en todas las estaciones.

El diseño único de la banda de rodadura, con cortes profundos y cuatro tacos, y los compuestos exclusivos para el invierno ofrecen una frenada superior en hielo o nieve, y evitan que se acumulen piedras durante el uso en todas las estaciones.

La baja relación de huecos y la gran huella de EARTHMAX SR 22 AS proporcionan una tracción y estabilidad excelentes, con un desgaste uniforme y una vida de neumático prolongada.

UM

US Standard

Construction

 RADIAL

Machinery

OTR: Motoniveladora • Pala cargadora

Version	CUT RESISTANT COMPOUND
Type	TL
Tyre Size	17.5 R 25
LI/SS	167 B/153 A8/182 A2

Dimensions US Standard

Usa code	94069613
Overall Width (inch)	17.5
Overall Diameter (inch)	53.1
Static Loaded Radius (inch)	23.4
Rolling Circumference (inch)	157.9
Rim Rec	14.00/1.5
Star Rating	**/**/**
TRA Code	E2/G2/L2

Load capacity (lbs)

mph / psi	18	22	25	29	33	36	40	44	58	62	65	69	73	76	80	83	87	91	94
30	-	-	-	-	-	-	-	-	9650	10200	10500	11000	11400	12000	-	-	-	-	-
25	4080	4680	5200	5840	6400	6800	7400	8050	-	-	-	-	-	-	-	-	-	-	-
5	-	-	-	-	-	-	-	-	-	-	-	-	-	16100	16500	17100	17600	18200	18700

Printed on 23/04/2024 17:02

All product data contained in this publication are for information purposes only and may be modified at any time without prior notice. Balkrishna Industries Ltd. or any of its subsidiary companies does not undertake any responsibility or liability for undetected errors and/or misprints. All rights reserved. The materials and contents of this publication and the website are the exclusive property of Balkrishna Industries Ltd. and are protected by industrial and/or intellectual property laws. The user is not permitted to copy, reproduce, transfer, upload, make use of, publish or spread any contents, in whole or in part, on paper format, electronic format or otherwise without prior written consent by Balkrishna Industries Ltd..