

EARTHMAX SR 22 - Especificaciones técnicas



Description

EARTHMAX SR 22 (G-2/L-2) es un neumático radial **All Steel** particularmente proyectado para las motoniveladoras y cargadoras que operan en condiciones invernales extremas en la nieve o en el hielo. Los operadores apreciarán la excelente tracción y la extraordinaria estabilidad garantizadas por el dibujo de la banda de rodadura ancho y no-direccional.

UM

International Standard

Construction

 RADIAL

Machinery

Industrial: Buldócer • Motoniveladora • Pala cargadora
OTR: Buldócer • Motoniveladora • Pala cargadora

Version	CUT RESISTANT COMPOUND
Type	TL
Tyre Size	14.00 R 24
LI/SS	153 A8/175 A2

Dimensions International Standard

Overall Width (mm)	366
Overall Diameter (mm)	1370
Static Loaded Radius (mm)	625
Rolling Circumference (mm)	4141
Rim Rec	8.00 TG
Rim Alt	9.00 GR , 10.00 VA
Star Rating	*
TRA Code	G2/L2

Load capacity (Kg)

km/h / bar	2.00	2.25	2.50	2.75	3.00	3.25	3.50	3.75	5.25	5.50
40	2240	2430	2650	2800	3000	3250	3350	3650	-	-
10	-	-	-	-	-	-	-	-	6700	6900

Printed on 15/04/2024 23:26

All product data contained in this publication are for information purposes only and may be modified at any time without prior notice. Balkrishna Industries Ltd. or any of its subsidiary companies does not undertake any responsibility or liability for undetected errors and/or misprints. All rights reserved. The materials and contents of this publication and the website are the exclusive property of Balkrishna Industries Ltd. and are protected by industrial and/or intellectual property laws. The user is not permitted to copy, reproduce, transfer, upload, make use of, publish or spread any contents, in whole or in part, on paper format, electronic format or otherwise without prior written consent by Balkrishna Industries Ltd..