

EARTHMAX SR 22 - Especificaciones técnicas



Description

EARTHMAX SR 22 (G-2/L-2) es un neumático radial **All Steel** particularmente proyectado para las motoniveladoras y cargadoras que operan en condiciones invernales extremas en la nieve o en el hielo. Los operadores apreciarán la excelente tracción y la extraordinaria estabilidad garantizadas por el dibujo de la banda de rodadura ancho y no-direccional.

UM

International Standard

Construction

 RADIAL

Machinery

Industrial: Buldócer • Motoniveladora • Pala cargadora
OTR: Buldócer • Motoniveladora • Pala cargadora

Version	CUT RESISTANT COMPOUND
Type	TL
Tyre Size	23.5 R 25
LI/SS	170 A8/195 A2

Dimensions International Standard

Overall Width (mm)	610
Overall Diameter (mm)	1614
Static Loaded Radius (mm)	709
Rolling Circumference (mm)	4863
Rim Rec	19.50/2.5
Star Rating	*
TRA Code	G2/L2

Load capacity (Kg)

km/h / bar	1.25	1.50	1.75	2.00	2.25	2.50	2.75	3.00	4.00	4.25	4.50	4.75	5.00
40	3150	3550	4000	4500	4875	5300	5600	6000	-	-	-	-	-
10	-	-	-	-	-	-	-	-	10300	10600	11200	11500	12150

Printed on 26/04/2024 9:49

All product data contained in this publication are for information purposes only and may be modified at any time without prior notice. Balkrishna Industries Ltd. or any of its subsidiary companies does not undertake any responsibility or liability for undetected errors and/or misprints. All rights reserved. The materials and contents of this publication and the website are the exclusive property of Balkrishna Industries Ltd. and are protected by industrial and/or intellectual property laws. The user is not permitted to copy, reproduce, transfer, upload, make use of, publish or spread any contents, in whole or in part, on paper format, electronic format or otherwise without prior written consent by Balkrishna Industries Ltd..