

EARTHMAX SR 30 - Especificaciones técnicas



Description

EARTHMAX SR 30 (E-3/L-3) es un neumático radial **All Steel** proyectado para un doble empleo, tanto con cargadoras como con volquetes articulados. Los cinturones de acero multiestrato y el dibujo rígido con bloques aseguran una excelente tracción, estabilidad y durabilidad. La especial mezcla resistente al corte, hace que EARTHMAX SR 30 sea la solución ideal para trabajar en condiciones operativas especiales.

UM

International Standard

Construction

 RADIAL

Machinery

OTR: Volquete articulado • Buldócer • Pala cargadora

Version	CUT RESISTANT COMPOUND
Type	TL
Tyre Size	26.5 R 25
LI/SS	202 A2

Dimensions International Standard

Overall Width (mm)	689
Overall Diameter (mm)	1742
Static Loaded Radius (mm)	766
Rolling Circumference (mm)	5200
Rim Rec	22.00/3.0
Star Rating	*
TRA Code	L3
Tread Depth	38

Load capacity (Kg)

km/h / bar	4.00	4.25	4.50	4.75	5.00
10	12850	13200	14000	14500	15000

Rolling Circumference & SLR values are at rated Load and inflation pressure. These values may vary at different Load and pressure condition.

Printed on 11/05/2025 17:14

All product data contained in this publication are for information purposes only and may be modified at any time without prior notice. Balkrishna Industries Ltd. or any of its subsidiary companies does not undertake any responsibility or liability for undetected errors and/or misprints. All rights reserved. The materials and contents of this publication and the website are the exclusive property of Balkrishna Industries Ltd. and are protected by industrial and/or intellectual property laws. The user is not permitted to copy, reproduce, transfer, upload, make use of, publish or spread any contents, in whole or in part, on paper format, electronic format or otherwise without prior written consent by Balkrishna Industries Ltd..