

## EARTHMAX SR 313 - Especificaciones técnicas



### Description

EARTHMAX SR 313 es un neumático radial All Steel diseñado específicamente para volquetes articulados y las cargadoras que operan en condiciones rocosas duras. Su compuesto resistente a los cortes y el diseño especial de la banda de rodadura protegen contra cortes y daños, además de ofrecer propiedades de autolimpieza. Su diseño de hombro cuadrado maximiza el contacto con el suelo para lograr una excelente maniobrabilidad. La estructura radial All Steel con correas de acero de varias capas garantiza una mayor durabilidad. EARTHMAX SR 313 es el neumático ideal para las operaciones de arrastre y carga y transporte.

### UM

US Standard

### Construction

 RADIAL

### Machinery

OTR: Volquete articulado • Pala cargadora

Version	CUT RESISTANT COMPOUND
Type	TL
Tyre Size	15.5 R 25
LI/SS	160 B/169 A2

## Dimensions US Standard

Usa code	94066964
TMPH	92
Overall Width (inch)	15.5
Overall Diameter (inch)	49.8
Static Loaded Radius (inch)	22.3
Rolling Circumference (inch)	150.5
Rim Rec	12.00/1.3
Star Rating	**/*
TRA Code	E3/L3

## Load capacity (lbs)

mph / psi	58	62	65	69	73	76
30	8050	8550	8800	9350	9650	9900
5	11000	11400	12000	12300	12800	-

Printed on 28/04/2024 0:30

All product data contained in this publication are for information purposes only and may be modified at any time without prior notice. Balkrishna Industries Ltd. or any of its subsidiary companies does not undertake any responsibility or liability for undetected errors and/or misprints. All rights reserved. The materials and contents of this publication and the website are the exclusive property of Balkrishna Industries Ltd. and are protected by industrial and/or intellectual property laws. The user is not permitted to copy, reproduce, transfer, upload, make use of, publish or spread any contents, in whole or in part, on paper format, electronic format or otherwise without prior written consent by Balkrishna Industries Ltd..