

EARTHMAX SR 31 - Ficha técnica



Description

EARTHMAX SR 31 es un neumático All Steel radial particularmente proyectado para dúmpers rígidos y palas cargadoras. Los cinturones de acero multiestrato aseguran una extraordinaria fuerza y estabilidad, mientras que el dibujo no-direccional rígido de bloques garantiza una excelente tracción y maniobrabilidad, incluso sobre un terreno de barro. Además del extraordinario confort en la conducción, EARTHMAX SR 31 se caracteriza también por una mezcla especial de la banda de rodadura, particularmente resistente a los cortes y al calor. La estructura radial de la carcasa ofrece además una baja resistencia al rodamiento, con un consecuente y significativo ahorro de carburante.

UM

US Standard

Construction

 RADIAL

Machinery

Industrial: Buldócer • Pala cargadora

OTR: Volquete articulado • Buldócer • Pala cargadora

SIZE	Version	USACode	TRA Code	Star R	LI/SS	RIM REC	RIM ALT	OW	OD	SLR	RC	Type	TMPH
20.5 R 25	CUT RESISTANT COMPOUND	94060610	E3/L3	**/*	177 B/186 A2	17.00/2.0	--	21.3	58.3	26.1	175.2	TL	116
23.5 R 25	CUT RESISTANT COMPOUND	94048434	E3/L3	**/*	185 B/195 A2	19.50/2.5	-	24.1	63.3	28	188.9	TL	137
26.5 R 25	CUT RESISTANT COMPOUND	94054381	L3	**	209 A2	22.00/3.0		27.1	68.6	30.2	204.7	TL	0
26.5 R 25	CUT RESISTANT COMPOUND	94053735	E3/L3	**/*	193 B/202 A2	22.00/3.0		27.1	68.6	30.2	204.7	TL	158
29.5 R 25	CUT RESISTANT COMPOUND	94054398	L3	**	216 A2	25.00/3.5		30.1	73.3	32.2	218.7	TL	0
29.5 R 25	CUT RESISTANT COMPOUND	94053742	E3/L3	**/*	200 B/208 A2	25.00/3.5		30.1	73.3	32.2	218.7	TL	185

Rolling Circumference & SLR values are at rated Load and inflation pressure. These values may vary at different Load and pressure condition.

Printed on 06/12/2024 4:56

All product data contained in this publication are for information purposes only and may be modified at any time without prior notice. Balkrishna Industries Ltd. or any of its subsidiary companies does not undertake any responsibility or liability for undetected errors and/or misprints. All rights reserved. The materials and contents of this publication and the website are the exclusive property of Balkrishna Industries Ltd. and are protected by industrial and/or intellectual property laws. The user is not permitted to copy, reproduce, transfer, upload, make use of, publish or spread any contents, in whole or in part, on paper format, electronic format or otherwise without prior written consent by Balkrishna Industries Ltd..