

## EARTHMAX SR 32 - Ficha técnica



### Description

EARTHMAX SR 32 es un neumático radial de base ancha no direccional para las mototraillas. Este neumático se caracteriza por una robusta carcasa All Steel y una mezcla específicamente formulada que aseguran una excelente resistencia a los cortes y las laceraciones así como durabilidad. Otras ventajas son tracción y flotación excepcionales también en condiciones de trabajo pesadas.

### UM

US Standard

### Construction

 RADIAL

### Machinery

OTR: Mototrailla

SIZE	Version	USACode	TRA Code	Star R	LI/SS	RIM REC	RIM ALT	OW	OD	SLR	RC	Type	TMPH
<b>29.5 R 29</b>	CUT RESISTANT COMPOUND	94066216	E3	**	202 B	25.00/3.5	24.00/3.5	30.1	78	34.8	236.6	TL	197
<b>33.25 R 29</b>	CUT RESISTANT COMPOUND	94057986	E3	**	209 B	27.00/3.5	26.00/3.5	33.3	81.9	36	246.1	TL	237
<b>37.25 R 35</b>	CUT RESISTANT COMPOUND	94064243	E3	**	218 B	31.00/4.0		37.9	93.7	41.8	284.6	TL	310
<b>40.5/75 R 39</b>	CUT RESISTANT COMPOUND	94066506	E3	**	225 B	32.00/4.5		38.8	102.8	45.8	312	TL	346
<b>40.5/75 R 39</b>	STANDARD COMPOUND	94069392	E3	**	225 B	32.00/4.5		38.8	102.8	45.8	312	TL	472

Printed on 13/04/2024 21:58

All product data contained in this publication are for information purposes only and may be modified at any time without prior notice. Balkrishna Industries Ltd. or any of its subsidiary companies does not undertake any responsibility or liability for undetected errors and/or misprints. All rights reserved. The materials and contents of this publication and the website are the exclusive property of Balkrishna Industries Ltd. and are protected by industrial and/or intellectual property laws. The user is not permitted to copy, reproduce, transfer, upload, make use of, publish or spread any contents, in whole or in part, on paper format, electronic format or otherwise without prior written consent by Balkrishna Industries Ltd..