EARTHMAX SR 33 PLUS - Ficha técnica

Description

EARTHMAX SR 33 PLUS es un neumático radial con un particular dibujo en bloques múltiplos proyectado para garantizar una excelente flotación sobre los terrenos blandos, arenosos o fangosos. La carcasa robusta All Steel se distingue por la excelente durabilidad y la resistencia contra cortes y pinchazos. EARTHMAX SR 33 PLUS ofrece una óptima estabilidad, así como extraordinarias propiedades de autolimpieza.

UM

US Standard

Construction

RADIAL

Machinery

Industrial: Vehículo universal

SIZE	Version	USACode	LI/SS	RIM REC	RIM ALT	OW	OD	SLR	RC	Type	ECE
16.00 R 20	STANDARD	94064038	173/170 G	11.25	10.00W, 10.0	17.6	51.6	22.9	156.5	TL	E11-54R-0017916

Printed on 26/04/2024 22:14

All product data contained in this publication are for information purposes only and may be modified at any time without prior notice. Balkrishna Industries Ltd. or any of its subsidiary companies does not undertake any responsibility or liability for undetected errors and/or misprints. All rights reserved. The materials and contents of this publication and the website are the exclusive property of Balkrishna Industries Ltd. and are protected by industrial and/or intellectual property laws. The user is not permitted to copy, reproduce, transfer, upload, make use of, publish or spread any contents, in whole or in part, on paper format, electronic format or otherwise without prior written consent by Balkrishna Industries Ltd..