

## EARTHMAX SR 33 - Especificaciones técnicas



### Description

Earthmax SR 33 es un neumático radial para vehículos universales. El particular dibujo en bloques ha sido proyectado para garantizar una excelente tracción sobre los terrenos blandos, arenosos o fangosos. Earthmax SR 33 ofrece una óptima estabilidad, así como extraordinarias propiedades de auto limpieza. La carcasa All Steel se distingue por la excelente durabilidad y la resistencia contra cortes y pinchazos.

### UM

US Standard

### Construction

 RADIAL

### Machinery

Industrial: Vehículo universal

Version	STANDARD
Type	TL
Tyre Size	335/80 R 20
LI/SS	150 K

## Dimensions US Standard

Usa code	94059478
Overall Width (inch)	13.2
Overall Diameter (inch)	41.2
Static Loaded Radius (inch)	18.3
Rolling Circumference (inch)	123.8
Rim Rec	11
ECE	E11-54R-0016679

## Load capacity (lbs)

mph / psi	94
68	7400

Printed on 19/04/2024 20:04

All product data contained in this publication are for information purposes only and may be modified at any time without prior notice. Balkrishna Industries Ltd. or any of its subsidiary companies does not undertake any responsibility or liability for undetected errors and/or misprints. All rights reserved. The materials and contents of this publication and the website are the exclusive property of Balkrishna Industries Ltd. and are protected by industrial and/or intellectual property laws. The user is not permitted to copy, reproduce, transfer, upload, make use of, publish or spread any contents, in whole or in part, on paper format, electronic format or otherwise without prior written consent by Balkrishna Industries Ltd..