

## EARTHMAX SR 33 - Ficha técnica



### Description

Earthmax SR 33 es un neumático radial para vehículos universales. El particular dibujo en bloques ha sido proyectado para garantizar una excelente tracción sobre los terrenos blandos, arenosos o fangosos. Earthmax SR 33 ofrece una óptima estabilidad, así como extraordinarias propiedades de auto limpieza. La carcasa All Steel se distingue por la excelente durabilidad y la resistencia contra cortes y pinchazos.

### UM

US Standard

### Construction

 RADIAL

### Machinery

Industrial: Vehículo universal

SIZE	Version	USACode	LI/SS	RIM REC	RIM ALT	OW	OD	SLR	RC	Type	ECE
<b>14.00 R 20</b>	STANDARD	94057757	164/160 J	10.0	9.0, 10.00W	15.4	49.2	22.7	151.2	TL	E11-54R-0016678
<b>335/80 R 20</b>	STANDARD	94059478	150 K	11		13.2	41.2	18.3	123.8	TL	E11-54R-0016679
<b>365/80 R 20 (14.5 R 20)</b>	STANDARD	94061907	152 K	11		14.2	43.1	19.5	130.6	TL	E11-54R-0017314
<b>395/85 R 20</b>	STANDARD	94050611	168 J	10.00W	10.00HF	15.5	46.6	21.2	141.3	TL	E11-54R-0017315

Printed on 19/04/2024 20:38

All product data contained in this publication are for information purposes only and may be modified at any time without prior notice. Balkrishna Industries Ltd. or any of its subsidiary companies does not undertake any responsibility or liability for undetected errors and/or misprints. All rights reserved. The materials and contents of this publication and the website are the exclusive property of Balkrishna Industries Ltd. and are protected by industrial and/or intellectual property laws. The user is not permitted to copy, reproduce, transfer, upload, make use of, publish or spread any contents, in whole or in part, on paper format, electronic format or otherwise without prior written consent by Balkrishna Industries Ltd..