

EARTHMAX SR 34 - Especificaciones técnicas



Description

EARTHMAX SR 34 es un neumático radial All Steel especialmente proyectado para los volquetes rígidos que operan en diversas aplicaciones, como las minas, las canteras, el sector forestal y el transporte. El dibujo no direccional de la banda de rodadura proporciona una excelente tracción y estabilidad en cualquier tipo de terreno. EARTHMAX SR 34 es ideal para manipular cargas pesadas. La sólida carcasa All Steel presenta una excelente resistencia al desgaste y contra cortes y pinchazos. Su talón reforzado y el particular diseño del hombro contribuyen a un ciclo de vida más largo del neumático, incluso en las condiciones de servicio pesado exigentes.

UM

US Standard

Construction

 RADIAL

Machinery

OTR: Dúmper rígido

Version	CUT RESISTANT COMPOUND
Type	TL
Tyre Size	16.00 R 25
LI/SS	177 B

Dimensions US Standard

Usa code	94070732
TMPH	130
Overall Width (inch)	17.3
Overall Diameter (inch)	59.4
Static Loaded Radius (inch)	27.3
Rolling Circumference (inch)	180.1
Rim Rec	11.25/2.0
Star Rating	**
TRA Code	E3+

Load capacity (lbs)

mph / psi	73	76	80	83	87	91	94	98	102
30	12300	12800	13200	13900	14300	14800	15200	15700	16100

Printed on 04/05/2024 17:48

All product data contained in this publication are for information purposes only and may be modified at any time without prior notice. Balkrishna Industries Ltd. or any of its subsidiary companies does not undertake any responsibility or liability for undetected errors and/or misprints. All rights reserved. The materials and contents of this publication and the website are the exclusive property of Balkrishna Industries Ltd. and are protected by industrial and/or intellectual property laws. The user is not permitted to copy, reproduce, transfer, upload, make use of, publish or spread any contents, in whole or in part, on paper format, electronic format or otherwise without prior written consent by Balkrishna Industries Ltd..