

EARTHMAX SR 35 - Especificaciones técnicas



Description

Earthmax SR 35 es un neumático radial All Steel de bajo perfil, particularmente proyectado para dúmpers articulados y cargadoras de ruedas. Es ideal para las operaciones que requieren una excelente tracción y flotación. Earthmax SR 35 asegura una excelente tracción y estabilidad. Gracias a la robusta carcasa con cinturones de acero, el neumático garantiza una extraordinaria durabilidad y resistencia contra desgarres y pinchazos.

UM

International Standard

Construction

 RADIAL

Machinery

OTR: Volquete articulado • Buldócer • Pala cargadora

Version	CUT RESISTANT COMPOUND
Type	TL
Tyre Size	775/65 R 29
LI/SS	195 B

Dimensions International Standard

TKPH	220
Overall Width (mm)	775
Overall Diameter (mm)	1752
Static Loaded Radius (mm)	787
Rolling Circumference (mm)	5311
Rim Rec	24.00/3.5
Rim Alt	24.00/3.0, 25.00/3.5
Star Rating	**
TRA Code	E3

Load capacity (Kg)

km/h / bar	4.00	4.25	4.50	4.75
50	10900	11200	11800	12150

Printed on 30/04/2024 0:45

All product data contained in this publication are for information purposes only and may be modified at any time without prior notice. Balkrishna Industries Ltd. or any of its subsidiary companies does not undertake any responsibility or liability for undetected errors and/or misprints. All rights reserved. The materials and contents of this publication and the website are the exclusive property of Balkrishna Industries Ltd. and are protected by industrial and/or intellectual property laws. The user is not permitted to copy, reproduce, transfer, upload, make use of, publish or spread any contents, in whole or in part, on paper format, electronic format or otherwise without prior written consent by Balkrishna Industries Ltd..