

## EARTHMAX SR 35 - Ficha técnica



### Description

Earthmax SR 35 es un neumático radial All Steel de bajo perfil, particularmente proyectado para dúmpers articulados y cargadoras de ruedas. Es ideal para las operaciones que requieren una excelente tracción y flotación. Earthmax SR 35 asegura una excelente tracción y estabilidad. Gracias a la robusta carcasa con cinturones de acero, el neumático garantiza una extraordinaria durabilidad y resistencia contra desgarres y pinchazos.

### UM

US Standard

### Construction

 RADIAL

### Machinery

OTR: Volquete articulado • Buldócer • Pala cargadora

SIZE	Version	USACode	TRA Code	Star R	LI/SS	RIM REC	RIM ALT	OW	OD	SLR	RC	Type	TMPH
650/65 R 25 (25/65 R 25)	CUT RESISTANT COMPOUND	94058587	E3	**	180 B	19.50/2.5		25	59	26.3	176.9	TL	138
650/65 R 25 (25/65 R 25)	CUT RESISTANT COMPOUND	94058631	E3/L3	***	180 B/193 A2	19.50/2.5		25	59	26.3	176.9	TL	138
650/65 R 25 (25/65 R 25)	CUT RESISTANT COMPOUND	94058624	L3	*	193 A2	19.50/2.5		25	59	26.3	176.9	TL	0
750/65 R 25 (30/65 R 25)	CUT RESISTANT COMPOUND	94051786	E3	**	190 B	24.00/3.0	22.00/3.0,25.00/3.0	29.1	63	28.1	189.1	TL	153
750/65 R 25 (30/65 R 25)	CUT RESISTANT COMPOUND	94053636	E3/L3	***	190 B/202 A2	24.00/3.0	22.00/3.0 ; 25.00/3.0	29.1	63	28.1	189.1	TL	153
750/65 R 25 (30/65 R 25)	CUT RESISTANT COMPOUND	94071340	L3	**	209 A2	24.00/3.0	22.00/3.0,25.00/3.0	29.1	63	28.1	189.1	TL	0
775/65 R 29	CUT RESISTANT COMPOUND	94064410	E3/L3	***	195 B/206 A2	24.00/3.5	24.00/3.0, 25.00/3.5	30.5	69	31	209.1	TL	151
775/65 R 29	CUT RESISTANT COMPOUND	94064427	E3	**	195 B	24.00/3.5	24.00/3.0, 25.00/3.5	30.5	69	31	209.1	TL	151
775/65 R 29	CUT RESISTANT COMPOUND	94064434	L3	*	206 A2	24.00/3.5	24.00/3.0, 25.00/3.5	30.5	69	31	209.1	TL	0
775/65 R 29	CUT RESISTANT COMPOUND	94067589	L3	**	213 A2	24.00/3.5	24.00/3.0, 25.00/3.5	30.5	69	31	209.1	TL	0
875/65 R 29 (35/65 R 29)	CUT RESISTANT COMPOUND	94059812	E3/L3	***	203 B/214 A2	27.00/3.50	27.00/3.0, 28.00/3.5	35	73.2	32.1	218.9	TL	191
875/65 R 29 (35/65 R 29)	CUT RESISTANT COMPOUND	94059805	E3	**	203 B	27.00/3.50	27.00/3.0, 28.00/3.5	35	73.2	32.1	218.9	TL	191
875/65 R 29 (35/65 R 29)	CUT RESISTANT COMPOUND	94059836	L3	*	214 A2	27.00/3.50	27.00/3.0, 28.00/3.5	35	73.2	32.1	218.9	TL	0

Printed on 29/04/2024 22:25

All product data contained in this publication are for information purposes only and may be modified at any time without prior notice. Balkrishna Industries Ltd. or any of its subsidiary companies does not undertake any responsibility or liability for undetected errors and/or misprints. All rights reserved. The materials and contents of this publication and the website are the exclusive property of Balkrishna Industries Ltd. and are protected by industrial and/or intellectual property laws. The user is not permitted to copy, reproduce, transfer, upload, make use of, publish or spread any contents, in whole or in part, on paper format, electronic format or otherwise without prior written consent by Balkrishna Industries Ltd..