

## EARTHMAX SR 412 - Especificaciones técnicas



### Description

EARTHMAX SR 412 (E-4/L-4) es un neumático radial All Steel particularmente proyectado para volquetes articulados, palas cargadoras y excavadoras. El dibujo único de la banda de rodadura con una profundidad de E-4 asegura una excelente tracción y una particular resistencia al calor. Gracias a la carcasa y los cinturones All Steel, EARTHMAX SR 412 puede soportar cargas muy pesadas y proporciona una excelente estabilidad y una elevada resistencia contra desgarres y pinchazos. EARTHMAX SR 412 se caracteriza por el hombro de forma cuadrada que ofrece un máximo contacto con el terreno así como una excelente maniobrabilidad.

### UM

US Standard

### Construction

 RADIAL

### Machinery

OTR: Volquete articulado • Buldócer • Pala cargadora

Version	CUT RESISTANT COMPOUND
Type	TL
Tyre Size	29.5 R 25
LI/SS	200 B

## Dimensions US Standard

Usa code	94062836
TMPH	173
Overall Width (inch)	30.1
Overall Diameter (inch)	73.4
Static Loaded Radius (inch)	32.8
Rolling Circumference (inch)	218.2
Rim Rec	25.00/3.5
Star Rating	**
TRA Code	E4

## Load capacity (lbs)

mph / psi	58	62	65	69	73	76
30	25400	26000	27600	28300	30000	30900

Printed on 26/04/2024 18:28

All product data contained in this publication are for information purposes only and may be modified at any time without prior notice. Balkrishna Industries Ltd. or any of its subsidiary companies does not undertake any responsibility or liability for undetected errors and/or misprints. All rights reserved. The materials and contents of this publication and the website are the exclusive property of Balkrishna Industries Ltd. and are protected by industrial and/or intellectual property laws. The user is not permitted to copy, reproduce, transfer, upload, make use of, publish or spread any contents, in whole or in part, on paper format, electronic format or otherwise without prior written consent by Balkrishna Industries Ltd..