

## EARTHMAX SR 41 - Especificaciones técnicas



### Description

EARTHMAX SR 41 es un neumático radial ideal para las palas cargadoras y los buldóceros en las aplicaciones de transporte, carga y empuje. Gracias a su estructura All Steel y al dibujo de bloques, EARTHMAX SR 41 ofrece una excelente resistencia a los pinchazos y una duración prolongada. Además de muchas horas operativas sin paradas de la máquina, este neumático asegura un confort excepcional. EARTHMAX SR 41 (E-4/L-4) es un neumático radial All Steel ideal para volquetes articulados, palas cargadoras y excavadoras.

### UM

US Standard

### Construction

 RADIAL

### Machinery

OTR: Volquete articulado • Buldócer • Pala cargadora • Volquete de perfil bajo

|           |                             |
|-----------|-----------------------------|
| Version   | CUT RESISTANT COMPOUND      |
| Type      | TL                          |
| Tyre Size | 875/65 R 29<br>(35/65 R 29) |
| LI/SS     | 221 A2                      |

## Dimensions US Standard

|                              |                      |
|------------------------------|----------------------|
| Usa code                     | 94064359             |
| Overall Width (inch)         | 34.6                 |
| Overall Diameter (inch)      | 73.4                 |
| Static Loaded Radius (inch)  | 33                   |
| Rolling Circumference (inch) | 223.6                |
| Rim Rec                      | 27.00/3.5            |
| Rim Alt                      | 27.00/3.0; 28.00/3.5 |
| Star Rating                  | **                   |
| TRA Code                     | L4                   |

## Load capacity (lbs)

| mph / psi | 73    | 76    | 80    | 83    | 87    | 91    |
|-----------|-------|-------|-------|-------|-------|-------|
| 5         | 48100 | 50700 | 52000 | 53600 | 55100 | 56800 |

Printed on 20/04/2024 0:43

All product data contained in this publication are for information purposes only and may be modified at any time without prior notice. Balkrishna Industries Ltd. or any of its subsidiary companies does not undertake any responsibility or liability for undetected errors and/or misprints. All rights reserved. The materials and contents of this publication and the website are the exclusive property of Balkrishna Industries Ltd. and are protected by industrial and/or intellectual property laws. The user is not permitted to copy, reproduce, transfer, upload, make use of, publish or spread any contents, in whole or in part, on paper format, electronic format or otherwise without prior written consent by Balkrishna Industries Ltd..