

## EARTHMAX SR 41 - Ficha técnica



### Description

EARTHMAX SR 41 es un neumático radial ideal para las palas cargadoras y los buldóceres en las aplicaciones de transporte, carga y empuje. Gracias a su estructura All Steel y al dibujo de bloques, EARTHMAX SR 41 ofrece una excelente resistencia a los pinchazos y una duración prolongada. Además de muchas horas operativas sin paradas de la máquina, este neumático asegura un confort excepcional. EARTHMAX SR 41 (E-4/L-4) es un neumático radial All Steel ideal para volquetes articulados, palas cargadoras y excavadoras.

### UM

International Standard

### Construction

 RADIAL

### Machinery

OTR: Volquete articulado • Buldócer • Pala cargadora •  
Volquete de perfil bajo

SIZE	Version	TRA Code	Star R	LI/SS	RIM REC	RIM ALT	OW	OD	SLR	RC	Type	TKPH
23.5 R 25	CUT RESISTANT COMPOUND	E4/L4	**/*	185 B/195 A2	19.50/2.5		615	1611	725	4790	TL	161
26.5 R 25	CUT RESISTANT COMPOUND	E4/L4	**/*	193 B/202 A2	22.00/3.0		678	1742	775	5150	TL	185
26.5 R 25	CUT RESISTANT COMPOUND (UMS)	E4	****		22.00/3.0		678	1742	775	5150	TL	
26.5 R 25	STANDARD COMPOUND	E4	**	193 B	22.00/3.0		678	1742	775	5150	TL	235
29.5 R 25	CUT RESISTANT COMPOUND	E4	**	200 B	25.00/3.5		761	1861	830	5510	TL	225
29.5 R 25	CUT RESISTANT COMPOUND	L4	***	221 A2	25.00/3.5		761	1861	830	5510	TL	
29.5 R 25	CUT RESISTANT COMPOUND	E4/L4	**/*	200 B/208 A2	25.00/3.5		761	1861	830	5510	TL	225
29.5 R 25	CUT RESISTANT COMPOUND (UMS)	E4	****		25.00/3.5		761	1861	830	5510	TL	
29.5 R 25	STANDARD COMPOUND	E4	**	200 B	25.00/3.5		761	1861	830	5510	TL	285
875/65 R 29 (35/65 R 29)	CUT RESISTANT COMPOUND	E4/L4	**/*	203 B/214 A2	27.00/3.50	27.00/3.0, 28.00/3.5	880	1865	837	5680	TL	240
875/65 R 29 (35/65 R 29)	CUT RESISTANT COMPOUND	E4	**	203 B	27.00/3.50	27.00/3.0, 28.00/3.5	880	1865	837	5680	TL	240
875/65 R 29 (35/65 R 29)	CUT RESISTANT COMPOUND	L4	*	214 A2	27.00/3.50	27.00/3.0, 28.00/3.5	880	1865	837	5680	TL	
875/65 R 29 (35/65 R 29)	CUT RESISTANT COMPOUND	L4	**	221 A2	27.00/3.5	27.00/3.0; 28.00/3.5	880	1865	837	5680	TL	
35/65 R 33	CUT RESISTANT COMPOUND (UMS)	E4	****		28.00/3.5	--	896	2063	926	6283	TL	

Printed on 19/04/2024 20:26

All product data contained in this publication are for information purposes only and may be modified at any time without prior notice. Balkrishna Industries Ltd. or any of its subsidiary companies does not undertake any responsibility or liability for undetected errors and/or misprints. All rights reserved. The materials and contents of this publication and the website are the exclusive property of Balkrishna Industries Ltd. and are protected by industrial and/or intellectual property laws. The user is not permitted to copy, reproduce, transfer, upload, make use of, publish or spread any contents, in whole or in part, on paper format, electronic format or otherwise without prior written consent by Balkrishna Industries Ltd..