

## EARTHMAX SR 431 - Especificaciones técnicas



### Description

EARTHMAX SR 431 (E-4) es un neumático radial All Steel particularmente proyectado para volquetes rígidos que operan en condiciones pesadas en las minas a cielo abierto y subterráneas. El dibujo no direccional de la banda de rodadura asegura una óptima tracción y estabilidad. Este neumático se caracteriza por una robusta carcasa All Steel y una mezcla específicamente formulada que aseguran una excelente resistencia a los cortes y las laceraciones, así como un ciclo de vida mas largo incluso los ambientes rocosos, abrasivos y hostiles.

### UM

International Standard

### Construction

 RADIAL

### Machinery

OTR: Dúmper rígido

Version	CUT RESISTANT COMPOUND (UMS)
Type	TL
Tyre Size	18.00 R 25

## Dimensions International Standard

Overall Width (mm)	520
Overall Diameter (mm)	1660
Static Loaded Radius (mm)	760
Rolling Circumference (mm)	5040
Rim Rec	13.00/2.5
Star Rating	****
TRA Code	E4

## Load capacity (Kg)

km/h / bar

\* In case of underground mine application, consult your servicing dealer or BKT representative.

Printed on 13/04/2024 1:50

All product data contained in this publication are for information purposes only and may be modified at any time without prior notice. Balkrishna Industries Ltd. or any of its subsidiary companies does not undertake any responsibility or liability for undetected errors and/or misprints. All rights reserved. The materials and contents of this publication and the website are the exclusive property of Balkrishna Industries Ltd. and are protected by industrial and/or intellectual property laws. The user is not permitted to copy, reproduce, transfer, upload, make use of, publish or spread any contents, in whole or in part, on paper format, electronic format or otherwise without prior written consent by Balkrishna Industries Ltd..