

EARTHMAX SR 431 - Ficha técnica



Description

EARTHMAX SR 431 (E-4) es un neumático radial All Steel particularmente proyectado para volquetes rígidos que operan en condiciones pesadas en las minas a cielo abierto y subterráneas. El dibujo no direccional de la banda de rodadura asegura una óptima tracción y estabilidad. Este neumático se caracteriza por una robusta carcasa All Steel y una mezcla específicamente formulada que aseguran una excelente resistencia a los cortes y las laceraciones, así como un ciclo de vida mas largo incluso los ambientes rocosos, abrasivos y hostiles.

UM

US Standard

Construction

 RADIAL

Machinery

OTR: Dúmpfer rígido

SIZE	Version	USACode	TRA Code	Star R	LI/SS	RIM REC	RIM ALT	OW	OD	SLR	RC	Type	TMPH
16.00 R 25	CUT RESISTANT COMPOUND	94062386	E4	**	177 B	11.25/2.0		17.8	60.3	28.1	183	TL	114
18.00 R 25	CUT RESISTANT COMPOUND	94060788	E4	**	185 B	13.00/2.5		20.5	65.4	29.9	198.4	TL	96
18.00 R 25	CUT RESISTANT COMPOUND (UMS)	94070794	E4	****		13.00/2.5		20.5	65.4	29.9	198.4	TL	0

Printed on 22/04/2024 17:43

All product data contained in this publication are for information purposes only and may be modified at any time without prior notice. Balkrishna Industries Ltd. or any of its subsidiary companies does not undertake any responsibility or liability for undetected errors and/or misprints. All rights reserved. The materials and contents of this publication and the website are the exclusive property of Balkrishna Industries Ltd. and are protected by industrial and/or intellectual property laws. The user is not permitted to copy, reproduce, transfer, upload, make use of, publish or spread any contents, in whole or in part, on paper format, electronic format or otherwise without prior written consent by Balkrishna Industries Ltd..