

EARTHMAX SR 45 H2 - Especificaciones técnicas



Description

EARTHMAX SR 45 H2 es un neumático All Steel particularmente proyectado para los volquetes rígidos. El dibujo único de la banda de rodadura con una profundidad de E-4 reduce el desgaste y minimiza las vibraciones y los ruidos. EARTHMAX SR 45 H2 es ideal para todas las operaciones que requieran una excelente tracción y estabilidad. Gracias a la estructura All Steel, lo neumático asegura una excelente resistencia a las laceraciones y los pinchazos, así como un ciclo de vida mas largo. Está disponible con mezcla estándar, resistente a los cortes o al calor.

UM

International Standard

Construction

RADIAL

Machinery

OTR: Dúmper rígido

Version	STANDARD COMPOUND
Type	TL
Tyre Size	24.00 R 35
LI/SS	212 B

Dimensions International Standard

TKPH	390
Overall Width (mm)	660
Overall Diameter (mm)	2180
Static Loaded Radius (mm)	978
Rolling Circumference (mm)	6597
Rim Rec	17.00/3.5
Rim Alt	---
Star Rating	***
TRA Code	E4

Load capacity (Kg)

km/h / bar	7.25	7.50	7.75	8.00
50	19000	19250	19500	20000

Printed on 29/11/2022 7:51

All product data contained in this publication are for information purposes only and may be modified at any time without prior notice. Balkrishna Industries Ltd. or any of its subsidiary companies does not undertake any responsibility or liability for undetected errors and/or misprints. All rights reserved. The materials and contents of this publication and the website are the exclusive property of Balkrishna Industries Ltd. and are protected by industrial and/or intellectual property laws. The user is not permitted to copy, reproduce, transfer, upload, make use of, publish or spread any contents, in whole or in part, on paper format, electronic format or otherwise without prior written consent by Balkrishna Industries Ltd..