

EARTHMAX SR 45 H2 - Ficha técnica



Description

EARTHMAX SR 45 H2 es un neumático All Steel particularmente proyectado para los volquetes rígidos. El dibujo único de la banda de rodadura con una profundidad de E-4 reduce el desgaste y minimiza las vibraciones y los ruidos. EARTHMAX SR 45 H2 es ideal para todas las operaciones que requieran una excelente tracción y estabilidad. Gracias a la estructura All Steel, lo neumático asegura una excelente resistencia a las laceraciones y los pinchazos, así como un ciclo de vida mas largo. Está disponible con mezcla estándar, resistente a los cortes o al calor.

UM

International Standard

Construction

RADIAL

Machinery

OTR: Dúmper rígido

SIZE	Version	TRA Code	Star R	LI/SS	RIM REC	RIM ALT	OW	OD	SLR	RC	Type	TKPH
24.00 R 35	CUT RESISTANT COMPOUND	E4	**	209 B	17.00/3.5	--	660	2180	978	6597	TL	333
24.00 R 35	CUT RESISTANT COMPOUND	E4	***	212 B	17.00/3.5	---	660	2180	978	6597	TL	333
24.00 R 35	HEAT RESISTANT COMPOUND	E4	**	209 B	17.00/3.5		660	2180	978	6597	TL	435
24.00 R 35	HEAT RESISTANT COMPOUND	E4	***	212 B	17.00/3.5	---	660	2180	978	6597	TL	435
24.00 R 35	STANDARD COMPOUND	E4	**	209 B	17.00/3.5	--	660	2180	978	6597	TL	390
24.00 R 35	STANDARD COMPOUND	E4	***	212 B	17.00/3.5	---	660	2180	978	6597	TL	390

Printed on 27/11/2022 12:26

All product data contained in this publication are for information purposes only and may be modified at any time without prior notice. Balkrishna Industries Ltd. or any of its subsidiary companies does not undertake any responsibility or liability for undetected errors and/or misprints. All rights reserved. The materials and contents of this publication and the website are the exclusive property of Balkrishna Industries Ltd. and are protected by industrial and/or intellectual property laws. The user is not permitted to copy, reproduce, transfer, upload, make use of, publish or spread any contents, in whole or in part, on paper format, electronic format or otherwise without prior written consent by Balkrishna Industries Ltd..