

## EARTHMAX SR 45 H2 - Ficha técnica



### Description

EARTHMAX SR 45 H2 es un neumático All Steel particularmente proyectado para los volquetes rígidos. El dibujo único de la banda de rodadura con una profundidad de E-4 reduce el desgaste y minimiza las vibraciones y los ruidos. EARTHMAX SR 45 H2 es ideal para todas las operaciones que requieran una excelente tracción y estabilidad. Gracias a la estructura All Steel, lo neumático asegura una excelente resistencia a las laceraciones y los pinchazos, así como un ciclo de vida mas largo. Está disponible con mezcla estándar, resistente a los cortes o al calor.

### UM

US Standard

### Construction

 RADIAL

### Machinery

OTR: Dúmpfer rígido

SIZE	Version	USACode	TRA Code	Star R	LI/SS	RIM REC	RIM ALT	OW	OD	SLR	RC	Type	TMPH
24.00 R 35	CUT RESISTANT COMPOUND	94063802	E4	***	212 B	17.00/3.5	---	26	85.8	38.5	259.7	TL	228
24.00 R 35	CUT RESISTANT COMPOUND	94060221	E4	**	209 B	17.00/3.5	--	26	85.8	38.5	259.7	TL	228
24.00 R 35	HEAT RESISTANT COMPOUND	94063826	E4	***	212 B	17.00/3.5	---	26	85.8	38.5	259.7	TL	298
24.00 R 35	HEAT RESISTANT COMPOUND	94060764	E4	**	209 B	17.00/3.5		26	85.8	38.5	259.7	TL	298
24.00 R 35	STANDARD COMPOUND	94063819	E4	***	212 B	17.00/3.5	---	26	85.8	38.5	259.7	TL	267
24.00 R 35	STANDARD COMPOUND	94059720	E4	**	209 B	17.00/3.5	--	26	85.8	38.5	259.7	TL	267

Printed on 23/04/2024 17:52

All product data contained in this publication are for information purposes only and may be modified at any time without prior notice. Balkrishna Industries Ltd. or any of its subsidiary companies does not undertake any responsibility or liability for undetected errors and/or misprints. All rights reserved. The materials and contents of this publication and the website are the exclusive property of Balkrishna Industries Ltd. and are protected by industrial and/or intellectual property laws. The user is not permitted to copy, reproduce, transfer, upload, make use of, publish or spread any contents, in whole or in part, on paper format, electronic format or otherwise without prior written consent by Balkrishna Industries Ltd..