

EARTHMAX SR 45 PLUS - Ficha técnica



Description

EARTHMAX SR 45 PLUS es un neumático radial All Steel especialmente proyectado para los volquetes rígidos y es ideal para las operaciones realizadas en largos recorridos. El dibujo de la banda de rodadura de EARTHMAX SR 45 PLUS minimiza las vibraciones y los ruidos.

UM

US Standard

Construction

RADIAL

Machinery

OTR: Dúmpster rígido

SIZE	Version	USACode	TRA Code	Star R	LI/SS	RIM REC	RIM ALT	OW	OD	SLR	RC	Type	TMPH
27.00 R 49	CUT RESISTANT COMPOUND	94045655	E4	**	223 B	19.50/4.0	--	29.4	106.4	47.8	318.7	TL	301
27.00 R 49	HEAT RESISTANT COMPOUND	94049813	E4	**	223 B	19.50/4.0	--	29.4	106.4	47.8	318.7	TL	418
27.00 R 49	STANDARD COMPOUND	94049806	E4	**	223 B	19.50/4.0	--	29.4	106.4	47.8	318.7	TL	370

Printed on 30/11/2022 11:49

All product data contained in this publication are for information purposes only and may be modified at any time without prior notice. Balkrishna Industries Ltd. or any of its subsidiary companies does not undertake any responsibility or liability for undetected errors and/or misprints. All rights reserved. The materials and contents of this publication and the website are the exclusive property of Balkrishna Industries Ltd. and are protected by industrial and/or intellectual property laws. The user is not permitted to copy, reproduce, transfer, upload, make use of, publish or spread any contents, in whole or in part, on paper format, electronic format or otherwise without prior written consent by Balkrishna Industries Ltd..