

## EARTHMAX SR 45 - Especificaciones técnicas



<b>Description</b>	EARTHMAX SR 45 es un neumático radial <i>All Steel</i> particularmente proyectado para los volquetes rígidos. EARTHMAX SR 45 es el neumático ideal para todas las operaciones que requieran una elevada tracción.
<b>UM</b>	US Standard
<b>Construction</b>	RADIAL
<b>Machinery</b>	OTR: Dúmper rígido

<b>Version</b>	HEAT RESISTANT COMPOUND
<b>Type</b>	TL
<b>Tyre Size</b>	18.00 R 33
<b>LI/SS</b>	191 B

### Dimensions US Standard

<b>Usa code</b>	94041855
<b>TMPH</b>	175
<b>Overall Width (inch)</b>	19.9
<b>Overall Diameter (inch)</b>	73.6
<b>Static Loaded Radius (inch)</b>	33.7
<b>Rolling Circumference (inch)</b>	220.8
<b>Rim Rec</b>	13.00/2.5
<b>Rim Alt</b>	--
<b>Star Rating</b>	**
<b>TRA Code</b>	E4

### Load capacity (lbs)

mph / psi	73	76	80	83	87	91	94	98	102
30	18700	19300	19800	20400	21500	22000	22700	23400	24000

*All product data contained in this publication are for information purposes only and may be modified at any time without prior notice. Balkrishna Industries Ltd. or any of its subsidiary companies does not undertake any responsibility or liability for undetected errors and/or misprints. All rights reserved. The materials and contents of this publication and the website are the exclusive property of Balkrishna Industries Ltd. and are protected by industrial and/or intellectual property laws. The user is not permitted to copy, reproduce, transfer, upload, make use of, publish or spread any contents, in whole or in part, on paper format, electronic format or otherwise without prior written consent by Balkrishna Industries Ltd..*