

## EARTHMAX SR 45 - Especificaciones técnicas



<b>Description</b>	EARTHMAX SR 45 es un neumático radial <i>All Steel</i> particularmente proyectado para los volquetes rígidos. EARTHMAX SR 45 es el neumático ideal para todas las operaciones que requieran una elevada tracción.
<b>UM</b>	US Standard
<b>Construction</b>	RADIAL
<b>Machinery</b>	OTR: Dúmper rígido

<b>Version</b>	STANDARD COMPOUND
<b>Type</b>	TL
<b>Tyre Size</b>	18.00 R 33
<b>LI/SS</b>	195 B

### Dimensions US Standard

<b>Usa code</b>	94064830
<b>TMPH</b>	151
<b>Overall Width (inch)</b>	19.9
<b>Overall Diameter (inch)</b>	73.6
<b>Static Loaded Radius (inch)</b>	33.7
<b>Rolling Circumference (inch)</b>	220.8
<b>Rim Rec</b>	13.00/2.5
<b>Star Rating</b>	***
<b>TRA Code</b>	E4

### Load capacity (lbs)

mph / psi	105	109	112	116
30	24700	25400	26000	26800

*publication and the website are the exclusive property of Balkrishna Industries Ltd. and are protected by industrial and/or intellectual property laws. The user is not permitted to copy, reproduce, transfer, upload, make use of, publish or spread any contents, in whole or in part, on paper format, electronic format or otherwise without prior written consent by Balkrishna Industries Ltd..*