

## **EARTHMAX SR 468 - Especificaciones técnicas**



### *Description*

EARTHMAX SR 468 es un neumático radial All Steel diseñado especialmente para camiones volquete rígidos. Su exclusivo diseño de la banda de rodadura con compuestos especiales la hace perfecta para condiciones mineras duras y rocosas. Sus tacos con ranuras circunferenciales y bloques entrelazados garantizan una disipación eficaz del calor. Además, el robusto hombro cuadrado ayuda a expulsar las piedras sueltas para proteger el neumático contra daños. EARTHMAX SR 468 se ha desarrollado con la tecnología de vanguardia de BKT para soportar cargas pesadas, ofrecer una mayor vida útil y proporcionar resistencia a los cortes y pinchazos de las rocas.

### *UM*

International Standard

### *Construction*

RADIAL

### *Machinery*

OTR: Dúmper rígido

<i>Version</i>	CUT RESISTANT COMPOUND
<i>Type</i>	TL
<i>Tyre Size</i>	37.00 R 57
<i>LI/SS</i>	245 B

### **Dimensions International Standard**

<i>TKPH</i>	725
<i>Overall Width (mm)</i>	1030
<i>Overall Diameter (mm)</i>	3425
<i>Static Loaded Radius (mm)</i>	1520
<i>Rolling Circumference (mm)</i>	10315
<i>Rim Rec</i>	27.00/6.0
<i>Rim Alt</i>	29.00/6.0
<i>Star Rating</i>	**
<i>TRA Code</i>	E4

## Load capacity (Kg)

km/h / bar	5.50	5.75	6.00	6.25	6.50	6.75	7.00
50	43750	45000	46250	47500	48750	50000	51500

Printed on 29/11/2022 8:46

All product data contained in this publication are for information purposes only and may be modified at any time without prior notice. Balkrishna Industries Ltd. or any of its subsidiary companies does not undertake any responsibility or liability for undetected errors and/or misprints. All rights reserved. The materials and contents of this publication and the website are the exclusive property of Balkrishna Industries Ltd. and are protected by industrial and/or intellectual property laws. The user is not permitted to copy, reproduce, transfer, upload, make use of, publish or spread any contents, in whole or in part, on paper format, electronic format or otherwise without prior written consent by Balkrishna Industries Ltd..