



# EARTHMAX SR 47 TP - Especificaciones técnicas

## Description

EARTHMAX SR 47 TP (E-4) es un neumático radial All Steel diseñado especialmente para camiones volquete rígidos que funcionan en condiciones que exigen la máxima tracción y resistencia a pinchazos. La profundidad de la banda de rodadura del E-4 garantiza una larga vida útil incluso en trayectos largos, lo que reduce el tiempo de inactividad y aumenta la productividad. EARTHMAX SR 47 TP es perfecto para cualquier tarea que exija tracción y estabilidad, especialmente en terrenos embarrados o resbaladizos. Disponible en compuestos estándar y resistente a los cortes.

## UM

US Standard

## Construction

 RADIAL

## Machinery

OTR: Dúmpers rígidos

Version	CUT RESISTANT COMPOUND
Type	TL
Tyre Size	24.00 R 35
LI/SS	209 B

## Dimensions US Standard

Usa code	94074204
TMPH	258
Overall Width (inch)	25.6
Overall Diameter (inch)	86
Static Loaded Radius (inch)	38.8
Rolling Circumference (inch)	260.8
Rim Rec	17.00/3.5
Rim Alt	--
Star Rating	**
TRA Code	E4

## Load capacity (lbs)

mph / psi	73	76	80	83	87	91	94	98	102
30	30900	32000	34200	35300	36400	37500	38600	39700	40800

Printed on 04/05/2024 3:55

All product data contained in this publication are for information purposes only and may be modified at any time without prior notice. Balkrishna Industries Ltd. or any of its subsidiary companies does not undertake any responsibility or liability for undetected errors and/or misprints. All rights reserved. The materials and contents of this publication and the website are the exclusive property of Balkrishna Industries Ltd. and are protected by industrial and/or intellectual property laws. The user is not permitted to copy, reproduce, transfer, upload, make use of, publish or spread any contents, in whole or in part, on paper format, electronic format or otherwise without prior written consent by Balkrishna Industries Ltd..