

EARTHMAX SR 475 - Especificaciones técnicas



Description

EARTHMAX SR 475 es un neumático radial All Steel particularmente proyectado para los dúmpers rígidos. Este neumático es ideal para los ambientes duros y rocosos particularmente con transportes de largo trayecto. El dibujo único de la banda de rodadura genera menos calor en climas cálidos y asegura una excelente tracción. La carcasa robusta y los cinturones de acero proporcionan una gran estabilidad y resistencia a cortes y pinchazos. EARTHMAX SR 475 ha sido proyectado con el hombro de forma cuadrada para asegurar un elevado confort de maniobrabilidad optimizando el contacto al suelo.

UM

International Standard

Construction

RADIAL

Machinery

OTR: Dúmpers rígidos

<i>Version</i>	STANDARD COMPOUND
<i>Type</i>	TL
<i>Tyre Size</i>	18.00 R 33
<i>LI/SS</i>	195 B

Dimensions International Standard

<i>TKPH</i>	292
<i>Overall Width (mm)</i>	490
<i>Overall Diameter (mm)</i>	1860
<i>Static Loaded Radius (mm)</i>	860
<i>Rolling Circumference (mm)</i>	5721
<i>Rim Rec</i>	13.00/2.5
<i>Star Rating</i>	***
<i>TRA Code</i>	E4

Load capacity (Kg)

km/h / bar	7.25	7.50	7.75	8.00
50	11200	11500	11800	12150

Printed on 29/11/2022 8:47

All product data contained in this publication are for information purposes only and may be modified at any time without prior notice. Balkrishna Industries Ltd. or any of its subsidiary companies does not undertake any responsibility or liability for undetected errors and/or misprints. All rights reserved. The materials and contents of this publication and the website are the exclusive property of Balkrishna Industries Ltd. and are protected by industrial and/or intellectual property laws. The user is not permitted to copy, reproduce, transfer, upload, make use of, publish or spread any contents, in whole or in part, on paper format, electronic format or otherwise without prior written consent by Balkrishna Industries Ltd..