

EARTHMAX SR 48 - Especificaciones técnicas



Description

EARTHMAX SR 48 es un neumático **All Steel** particularmente desarrollado y realizado para dúmpers rígidos. Asegura una mayor tracción y una extraordinaria resistencia al desgaste incluso en las difíciles operaciones realizadas en los ambientes rocosos. Este neumático es ideal para el transporte de cargas pesadas. El hombro de forma cuadrada protege el flanco contra los cortes y otros daños. Earthmax SR 48 muestra una robusta carcasa **All Steel** que ofrece una excepcional protección contra los golpes y las perforaciones causadas por las piedras, optimizando la productividad.

UM

International Standard

Construction

 RADIAL

Machinery

OTR: Dúmpers rígidos

Version	HEAT RESISTANT COMPOUND
Type	TL
Tyre Size	27.00 R 49
LI/SS	223 B

Dimensions International Standard

TKPH	600
Overall Width (mm)	738
Overall Diameter (mm)	2688
Static Loaded Radius (mm)	1225
Rolling Circumference (mm)	8165
Rim Rec	19.50/4.0
Rim Alt	--
Star Rating	**
TRA Code	E4

Load capacity (Kg)

km/h / bar	5.00	5.25	5.50	5.75	6.00	6.25	6.50	6.75	7.00
50	20600	21800	22400	23000	23600	25000	25750	26500	27250

Printed on 26/04/2024 7:13

All product data contained in this publication are for information purposes only and may be modified at any time without prior notice. Balkrishna Industries Ltd. or any of its subsidiary companies does not undertake any responsibility or liability for undetected errors and/or misprints. All rights reserved. The materials and contents of this publication and the website are the exclusive property of Balkrishna Industries Ltd. and are protected by industrial and/or intellectual property laws. The user is not permitted to copy, reproduce, transfer, upload, make use of, publish or spread any contents, in whole or in part, on paper format, electronic format or otherwise without prior written consent by Balkrishna Industries Ltd..