

## EARTHMAX SR 48 - Ficha técnica



### Description

EARTHMAX SR 48 es un neumático **All Steel** particularmente desarrollado y realizado para dúmpers rígidos. Asegura una mayor tracción y una extraordinaria resistencia al desgaste incluso en las difíciles operaciones realizadas en los ambientes rocosos. Este neumático es ideal para el transporte de cargas pesadas. El hombro de forma cuadrada protege el flanco contra los cortes y otros daños. Earthmax SR 48 muestra una robusta carcasa **All Steel** que ofrece una excepcional protección contra los golpes y las perforaciones causadas por las piedras, optimizando la productividad.

### UM

US Standard

### Construction

 RADIAL

### Machinery

OTR: Dúmpers rígidos

SIZE	Version	USACode	TRA Code	Star R	LI/SS	RIM REC	RIM ALT	OW	OD	SLR	RC	Type	TMPH
24.00 R 35	CUT RESISTANT COMPOUND	94060276	E4	**	209 B	17.00/3.5		26.2	85.8	39.1	260.7	TL	212
24.00 R 35	STANDARD COMPOUND	94059713	E4	**	209 B	17.00/3.5		26.2	85.8	39.1	260.7	TL	258
27.00 R 49	CUT RESISTANT COMPOUND	94053209	E4	**	223 B	19.50/4.0	--	29.1	105.8	48.2	321.5	TL	301
27.00 R 49	HEAT RESISTANT COMPOUND	94054312	E4	**	223 B	19.50/4.0	--	29.1	105.8	48.2	321.5	TL	411
27.00 R 49	STANDARD COMPOUND	94055142	E4	**	223 B	19.50/4.0	--	29.1	105.8	48.2	321.5	TL	349

Printed on 26/04/2024 4:59

All product data contained in this publication are for information purposes only and may be modified at any time without prior notice. Balkrishna Industries Ltd. or any of its subsidiary companies does not undertake any responsibility or liability for undetected errors and/or misprints. All rights reserved. The materials and contents of this publication and the website are the exclusive property of Balkrishna Industries Ltd. and are protected by industrial and/or intellectual property laws. The user is not permitted to copy, reproduce, transfer, upload, make use of, publish or spread any contents, in whole or in part, on paper format, electronic format or otherwise without prior written consent by Balkrishna Industries Ltd..