

EARTHMAX SR 50 - Especificaciones técnicas



Description

EARTHMAX SR 50 (L-5) es un neumático radial **All Steel** particularmente proyectado para cargadoras. Su resistente carcasa y los cordones de protección son ideales para las operaciones más exigentes. EARTHMAX SR 50 está realizado con una mezcla especialmente resistente a los cortes que reduce el desgaste y asegura un ciclo de vida más largo al neumático. Los operadores apreciarán también la excelente tracción, así como la estabilidad y una conducción más confortable.

UM

US Standard

Construction

 RADIAL

Machinery

OTR: Pala cargadora

Version	CUT RESISTANT COMPOUND
Type	TL
Tyre Size	26.5 R 25
LI/SS	202 A2

Dimensions US Standard

Usa code	94032303
Overall Width (inch)	27.2
Overall Diameter (inch)	69.8
Static Loaded Radius (inch)	31.7
Rolling Circumference (inch)	210
Rim Rec	22.00/3.0
Star Rating	*
TRA Code	L5

Load capacity (lbs)

mph / psi	58	62	65	69	73
5	28300	29100	30900	32000	33100

Printed on 22/02/2024 19:15

All product data contained in this publication are for information purposes only and may be modified at any time without prior notice. Balkrishna Industries Ltd. or any of its subsidiary companies does not undertake any responsibility or liability for undetected errors and/or misprints. All rights reserved. The materials and contents of this publication and the website are the exclusive property of Balkrishna Industries Ltd. and are protected by industrial and/or intellectual property laws. The user is not permitted to copy, reproduce, transfer, upload, make use of, publish or spread any contents, in whole or in part, on paper format, electronic format or otherwise without prior written consent by Balkrishna Industries Ltd..