

EARTHMAX SR 50 - Ficha técnica



Description

EARTHMAX SR 50 (L-5) es un neumático radial **All Steel** particularmente proyectado para cargadoras. Su resistente carcasa y los cordones de protección son ideales para las operaciones más exigentes. EARTHMAX SR 50 está realizado con una mezcla especialmente resistente a los cortes que reduce el desgaste y asegura un ciclo de vida más largo al neumático. Los operadores apreciarán también la excelente tracción, así como la estabilidad y una conducción más confortable.

UM

International Standard

Construction

 RADIAL

Machinery

OTR: Pala cargadora

SIZE	Version	TRA Code	Star R	LI/SS	RIM REC	RIM ALT	OW	OD	SLR	RC	Type
26.5 R 25	CUT RESISTANT COMPOUND	L5	*	202 A2	22.00/3.0		690	1772	806	5334	TL
26.5 R 25	CUT RESISTANT COMPOUND	L5	**	209 A2	22.00/3.0		690	1772	806	5334	TL
29.5 R 25	CUT RESISTANT COMPOUND	L5	*	208 A2	25.00/3.5		775	1901	862	5722	TL
29.5 R 25	CUT RESISTANT COMPOUND	L5	**	216 A2	25.00/3.5		775	1901	862	5722	TL

Printed on 22/02/2024 20:00

All product data contained in this publication are for information purposes only and may be modified at any time without prior notice. Balkrishna Industries Ltd. or any of its subsidiary companies does not undertake any responsibility or liability for undetected errors and/or misprints. All rights reserved. The materials and contents of this publication and the website are the exclusive property of Balkrishna Industries Ltd. and are protected by industrial and/or intellectual property laws. The user is not permitted to copy, reproduce, transfer, upload, make use of, publish or spread any contents, in whole or in part, on paper format, electronic format or otherwise without prior written consent by Balkrishna Industries Ltd..