

EARTHMAX SR 51 - Especificaciones técnicas



Description

EARTHMAX SR 51 (L-5) es un neumático radial **All Steel** particularmente desarrollado para cargadoras y buldóceres. EARTHMAX SR 51 es ideal para las operaciones más duras que requieran una adicional resistencia al corte, así como una protección de los flancos y una excepcional tracción.

UM

US Standard

Construction

 RADIAL

Machinery

OTR: Buldócer • Pala cargadora

| | |
|-----------|------------------------|
| Version | CUT RESISTANT COMPOUND |
| Type | TL |
| Tyre Size | 29.5 R 29 |
| LI/SS | 211 A2 |

Dimensions US Standard

| | |
|------------------------------|----------------------|
| Usa code | 94051113 |
| Overall Width (inch) | 30.6 |
| Overall Diameter (inch) | 78.3 |
| Static Loaded Radius (inch) | 33.1 |
| Rolling Circumference (inch) | 231.2 |
| Rim Rec | 25.00/3.5 |
| Rim Alt | 24.00/3.5, 26.00/3.5 |
| Star Rating | * |
| TRA Code | L5 |

Load capacity (lbs)

| mph / psi | 58 | 62 | 65 | 69 | 73 |
|-----------|-------|-------|-------|-------|-------|
| 5 | 36400 | 37500 | 39700 | 40800 | 43000 |

Printed on 29/04/2024 5:20

All product data contained in this publication are for information purposes only and may be modified at any time without prior notice. Balkrishna Industries Ltd. or any of its subsidiary companies does not undertake any responsibility or liability for undetected errors and/or misprints. All rights reserved. The materials and contents of this publication and the website are the exclusive property of Balkrishna Industries Ltd. and are protected by industrial and/or intellectual property laws. The user is not permitted to copy, reproduce, transfer, upload, make use of, publish or spread any contents, in whole or in part, on paper format, electronic format or otherwise without prior written consent by Balkrishna Industries Ltd..