

EARTHMAX SR 51 - Ficha técnica



Description

EARTHMAX SR 51 (L-5) es un neumático radial **All Steel** particularmente desarrollado para cargadoras y buldóceres. EARTHMAX SR 51 es ideal para las operaciones más duras que requieran una adicional resistencia al corte, así como una protección de los flancos y una excepcional tracción.

UM

International Standard

Construction

 RADIAL

Machinery

OTR: Buldócer • Pala cargadora

| SIZE | Version | TRA Code | Star R | LI/SS | RIM REC | RIM ALT | OW | OD | SLR | RC | Type |
|-----------------------------|------------------------|----------|--------|--------|-----------|----------------------|-----|------|-----|------|------|
| 17.5 R 25 | CUT RESISTANT COMPOUND | L5 | * | 176 A2 | 14.00/1.5 | | 437 | 1398 | 630 | 4110 | TL |
| 20.5 R 25 | CUT RESISTANT COMPOUND | L5 | * | 186 A2 | 17.00/2.0 | | 539 | 1545 | 703 | 4650 | TL |
| 23.5 R 25 | CUT RESISTANT COMPOUND | L5 | * | 195 A2 | 19.50/2.5 | | 612 | 1660 | 743 | 4882 | TL |
| 23.5 R 25 | CUT RESISTANT COMPOUND | L5 | ** | 201 A2 | 19.50/2.5 | | 612 | 1660 | 743 | 4882 | TL |
| 29.5 R 29 | CUT RESISTANT COMPOUND | L5 | * | 211 A2 | 25.00/3.5 | 24.00/3.5, 26.00/3.5 | 777 | 1990 | 842 | 5872 | TL |
| 875/65 R 29 (35/65 R 29) | CUT RESISTANT COMPOUND | L5 | ** | 221 A2 | 27.00/3.5 | 27.00/3.0; 28.00/3.5 | 878 | 1872 | 814 | 5616 | TL |
| 35/65 R 33 | CUT RESISTANT COMPOUND | L5 | ** | 224 A2 | 28.00/3.5 | | 905 | 2061 | 872 | 6082 | TL |
| 35/65 R 33 | CUT RESISTANT COMPOUND | L5 | *** | 229 A2 | 28.00/3.5 | | 905 | 2061 | 872 | 6082 | TL |

Rolling Circumference & SLR values are at rated Load and inflation pressure. These values may vary at different Load and pressure condition.

Printed on 11/11/2024 22:14

All product data contained in this publication are for information purposes only and may be modified at any time without prior notice. Balkrishna Industries Ltd. or any of its subsidiary companies does not undertake any responsibility or liability for undetected errors and/or misprints. All rights reserved. The materials and contents of this publication and the website are the exclusive property of Balkrishna Industries Ltd. and are protected by industrial and/or intellectual property laws. The user is not permitted to copy, reproduce, transfer, upload, make use of, publish or spread any contents, in whole or in part, on paper format, electronic format or otherwise without prior written consent by Balkrishna Industries Ltd..