

EARTHMAX SR 55 - Especificaciones técnicas



Description

EARTHMAX SR 55 (L-55) es un neumático radial All Steel especialmente proyectado para las palas cargadoras, los buldóceros y las cargadoras que operan en condiciones muy difíciles, como en las canteras, las minas y en los depósitos de chatarra. Gracias al dibujo de la banda de rodadura extra profundo y liso, EARTHMAX SR 55 puede alcanzar elevados niveles de productividad con menores tiempos de parada de la máquina. Los operadores de las máquinas apreciarán también estabilidad y tracción extraordinarias.

UM

International Standard

Construction

 RADIAL

Machinery

OTR: Buldócer • Cargadora LHD • Pala cargadora

Version	CUT RESISTANT COMPOUND
Type	TL
Tyre Size	17.5 R 25
LI/SS	188 A2

Dimensions International Standard

Overall Width (mm)	453
Overall Diameter (mm)	1399
Static Loaded Radius (mm)	630
Rolling Circumference (mm)	4211
Rim Rec	14.00/1.5
Star Rating	***
TRA Code	L5S

Load capacity (Kg)

km/h / bar	6.75	7.00	7.25	7.50	7.75	8.00
10	8750	9000	9250	9500	9750	10000

Printed on 23/04/2024 9:36

All product data contained in this publication are for information purposes only and may be modified at any time without prior notice. Balkrishna Industries Ltd. or any of its subsidiary companies does not undertake any responsibility or liability for undetected errors and/or misprints. All rights reserved. The materials and contents of this publication and the website are the exclusive property of Balkrishna Industries Ltd. and are protected by industrial and/or intellectual property laws. The user is not permitted to copy, reproduce, transfer, upload, make use of, publish or spread any contents, in whole or in part, on paper format, electronic format or otherwise without prior written consent by Balkrishna Industries Ltd..