

EARTHMAX SR 57 - Especificaciones técnicas



Description

EARTHMAX SR 57 es un neumático radial All Steel particularmente proyectado para las palas cargadoras, las buldóceres y los vehículos utilitarios que se utilizan en las minas subterráneas. Este neumático asegura una tracción superior, así como una excelente estabilidad y confort sobre las superficies rugosas y rocosas. La banda de rodadura extra profunda L-5, junto con la especial fórmula UMS (underground mine service) de la mezcla, garantizan una mayor resistencia al desgaste y una extraordinaria resistencia contra los cortes y los pinchazos causados por las rocas.

UM

US Standard

Construction

 RADIAL

Machinery

OTR: Buldócer • Cargadora LHD • Pala cargadora

Version	CUT RESISTANT COMPOUND
Type	TL
Tyre Size	18.00 R 25
LI/SS	204 A2

Dimensions US Standard

Usa code	94063307
Overall Width (inch)	20.3
Overall Diameter (inch)	65
Rim Rec	13.00/2.5
Star Rating	**
TRA Code	L5

Load capacity (lbs)

mph / psi	83	87	91	94	98	102	105	109	112	116	120
5	26800	27600	28300	29100	30000	30900	32000	33100	33600	34200	35300

Printed on 26/04/2024 12:24

All product data contained in this publication are for information purposes only and may be modified at any time without prior notice. Balkrishna Industries Ltd. or any of its subsidiary companies does not undertake any responsibility or liability for undetected errors and/or misprints. All rights reserved. The materials and contents of this publication and the website are the exclusive property of Balkrishna Industries Ltd. and are protected by industrial and/or intellectual property laws. The user is not permitted to copy, reproduce, transfer, upload, make use of, publish or spread any contents, in whole or in part, on paper format, electronic format or otherwise without prior written consent by Balkrishna Industries Ltd..