

EM 933 SUPER - Especificaciones técnicas



Description

EM 933 SUPER se ha diseñado especialmente para excavadoras en operaciones de excavación y carga. Su excepcional diseño de pared lateral, con un reborde que sobresale, permite el contacto estrecho entre dos neumáticos, lo que elimina la necesidad de un anillo de caucho especial para evitar la penetración de piedras. El exclusivo diseño de la banda de rodadura proporciona una tracción superior en condiciones exigentes. Otras prestaciones de EM 933 SUPER son el excelente confort de conducción y las propiedades de autolimpieza mejoradas.

UM

US Standard

Construction

 BIAS

Machinery

Industrial: Pala excavadora

Version	STANDARD
Type	TT
Tyre Size	290/90 - 20
LI/SS	152 B / 168 A2

Dimensions US Standard

Usa code	94070183
Ply Rating	18
Overall Width (inch)	11.6
Overall Diameter (inch)	41.5
Rim Rec	8.00
TRA Code	E2

Load capacity (lbs)

mph / psi	131
5	12350
30	7780

Printed on 20/04/2024 15:58

All product data contained in this publication are for information purposes only and may be modified at any time without prior notice. Balkrishna Industries Ltd. or any of its subsidiary companies does not undertake any responsibility or liability for undetected errors and/or misprints. All rights reserved. The materials and contents of this publication and the website are the exclusive property of Balkrishna Industries Ltd. and are protected by industrial and/or intellectual property laws. The user is not permitted to copy, reproduce, transfer, upload, make use of, publish or spread any contents, in whole or in part, on paper format, electronic format or otherwise without prior written consent by Balkrishna Industries Ltd..