

## EM 934 - Especificaciones técnicas



### Description

EM 934 ha sido particularmente proyectado para las excavadoras que se utilizan en la construcción de las carreteras, ofreciendo una excelente tracción lateral, así como extraordinarias cualidades de auto-limpieza. La mezcla especial de la banda de rodadura es particularmente resistente a los cortes y los desgarres, mientras que su robusta carcasa asegura una larga vida operativa al neumático.

### UM

US Standard

### Construction

 BIAS

### Machinery

Industrial: Pala excavadora

Version	SPECIAL
Type	TT
Tyre Size	10.00 - 20
LI/SS	146 B

## Dimensions US Standard

Usa code	94054145
Ply Rating	16
Overall Width (inch)	11
Overall Diameter (inch)	41.7
Static Loaded Radius (inch)	19.7
Rolling Circumference (inch)	126.3
Rim Rec	7.5
Rim Alt	7.0 ; 8.0
TRA Code	E2

## Load capacity (lbs)

mph / psi	109
30	6610

Printed on 20/04/2024 10:17

All product data contained in this publication are for information purposes only and may be modified at any time without prior notice. Balkrishna Industries Ltd. or any of its subsidiary companies does not undertake any responsibility or liability for undetected errors and/or misprints. All rights reserved. The materials and contents of this publication and the website are the exclusive property of Balkrishna Industries Ltd. and are protected by industrial and/or intellectual property laws. The user is not permitted to copy, reproduce, transfer, upload, make use of, publish or spread any contents, in whole or in part, on paper format, electronic format or otherwise without prior written consent by Balkrishna Industries Ltd..