

EM 937 (E3) - Ficha técnica



Description

EM 937 (E-3) ha sido particularmente desarrollado para las cargadoras y las ternas que se utilizan en las operaciones de excavación y carga, dependiendo de la medida. Este neumático se caracteriza por una excelente durabilidad y una óptima resistencia a los cortes y los desgarros.

UM

US Standard

Construction

 BIAS

Machinery

OTR: Dúmpfer rígido

SIZE	Version	USACode	TRA Code	PR	RIM REC	RIM ALT	OW	OD	SLR	RC	Type
14.00 - 25	STANDARD	94015443	E3/L3	28	10.00/1.5		14.8	53.9	24.4	161.6	TT
14.00 - 25	STANDARD	94015450	E3/L3	28	10.00/1.5		14.8	53.9	24.4	161.6	TL

Printed on 05/12/2023 22:55

All product data contained in this publication are for information purposes only and may be modified at any time without prior notice. Balkrishna Industries Ltd. or any of its subsidiary companies does not undertake any responsibility or liability for undetected errors and/or misprints. All rights reserved. The materials and contents of this publication and the website are the exclusive property of Balkrishna Industries Ltd. and are protected by industrial and/or intellectual property laws. The user is not permitted to copy, reproduce, transfer, upload, make use of, publish or spread any contents, in whole or in part, on paper format, electronic format or otherwise without prior written consent by Balkrishna Industries Ltd..