

F 240 - Especificaciones técnicas



Description

F 240 es un neumático forestal particularmente desarrollado para la manipulación de troncos. El diseño de la banda de rodadura asegura una excelente tracción y óptimas propiedades de autolimpieza, además de una buena maniobrabilidad. La excelente mezcla de la banda de rodadura garantiza una extraordinaria resistencia a los cortes y al desgaste, obteniendo una vida útil más larga del neumático. F 240 se caracteriza por una ancha área de contacto que se traduce en una mejor estabilidad.

UM

International Standard

Construction

❖ BIAS

Machinery

Agricultura: Cosechadora forestal

Version	STANDARD
Type	TT
Tyre Size	400 - 15.5 (400 - 15.5)

Dimensions International Standard

Ply Rating	12
Section Width (mm)	405
Overall Diameter (mm)	865
Rim Rec	AG 13.00
ECE	E11-106R-004260
TRA Code	LS2

Load capacity (Kg)

km/h / bar	3.80
30	3150

Printed on 26/04/2024 17:46

All product data contained in this publication are for information purposes only and may be modified at any time without prior notice. Balkrishna Industries Ltd. or any of its subsidiary companies does not undertake any responsibility or liability for undetected errors and/or misprints. All rights reserved. The materials and contents of this publication and the website are the exclusive property of Balkrishna Industries Ltd. and are protected by industrial and/or intellectual property laws. The user is not permitted to copy, reproduce, transfer, upload, make use of, publish or spread any contents, in whole or in part, on paper format, electronic format or otherwise without prior written consent by Balkrishna Industries Ltd..