

F 240 - Ficha técnica



Description

F 240 es un neumático forestal particularmente desarrollado para la manipulación de troncos. El diseño de la banda de rodadura asegura una excelente tracción y óptimas propiedades de autolimpieza, además de una buena maniobrabilidad. La excelente mezcla de la banda de rodadura garantiza una extraordinaria resistencia a los cortes y al desgaste, obteniendo una vida útil más larga del neumático. F 240 se caracteriza por una ancha área de contacto que se traduce en una mejor estabilidad.

UM

US Standard

Construction

❖ BIAS

Machinery

Agricultura: Cosechadora forestal

SIZE	Version	USACode	TRA Code	PR	RIM REC	RIM ALT	SW	OD	SLR	RC	Type	ECE
18 - 15.5	STANDARD	94052004	LS2	14	AG 13.00		17.7	39	16.9	115.4	TT	E11-106R-004259
400 - 15.5 (400 - 15.5)	STANDARD	94051588	LS2	12	AG 13.00		15.9	34.1	0	0	TT	E11-106R-004260

Rolling Circumference & SLR values are at rated Load and inflation pressure. These values may vary at different Load and pressure condition.

Printed on 14/02/2025 6:52

All product data contained in this publication are for information purposes only and may be modified at any time without prior notice. Balkrishna Industries Ltd. or any of its subsidiary companies does not undertake any responsibility or liability for undetected errors and/or misprints. All rights reserved. The materials and contents of this publication and the website are the exclusive property of Balkrishna Industries Ltd. and are protected by industrial and/or intellectual property laws. The user is not permitted to copy, reproduce, transfer, upload, make use of, publish or spread any contents, in whole or in part, on paper format, electronic format or otherwise without prior written consent by Balkrishna Industries Ltd..